



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : B01D 53/32, 53/36, B01J 19/08	A1	(11) International Publication Number: WO 92/19361 (43) International Publication Date: 12 November 1992 (12.11.92)
(21) International Application Number: PCT/US92/03490 (22) International Filing Date: 28 April 1992 (28.04.92) (30) Priority data: 694,090 1 May 1991 (01.05.91) US (71) Applicant: PLASMACHINES, INC. [US/US]; 11 Mercer Road, Natick, MA 01760 (US). (72) Inventor: RICH, Stanley, R. ; 23 Fairway Drive, P.O. Box 68, Grantham, NH 03753 (US). (74) Agent: LOUDERMILK, Alan, R.; Jenner & Block, One IBM Plaza, Chicago, IL 60611 (US).		(81) Designated States: AT (European patent), AU, BE (European patent), BG, BR, CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (European patent), IT (European patent), JP, KR, LU (European patent), MC (European patent), NL (European patent), RU, SE (European patent). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: EXHAUST TREATMENT SYSTEM AND METHOD (57) Abstract A moving fluid containing pollutants including NO _x compounds is subjected to a relatively low-power alternating-current dielectric discharge for a relatively long time duration. In this manner, pollutants are oxidized and dissociated while the temperature of the fluid is kept low enough to prevent the formation of new NO _x pollutants.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MI	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
CA	Canada	IT	Italy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark	MG	Madagascar		
ES	Spain				

- 1 -

EXHAUST TREATMENT SYSTEM AND METHOD

Technical Field

This invention relates to apparatus and method for reducing polluting substances such as NOx, hydrocarbons and carbon monoxide emissions in a fluid such as an exhaust gas or stack gas.

Background Art

Polluting agents in exhaust gases generated by internal combustion engines and in stack gases generated by power plants burning fossil fuels have seriously degraded air quality in many locations and created acid rain, smog and a host of other environmental problems. Two pollution components commonly found in exhaust and stack gases are nitrogen compounds such as nitric oxide and nitrogen dioxide (collectively called NOx), carbon monoxide and various hydrocarbon compounds which result from incomplete or imperfect combustion of the fossil fuels. Although these components are known to cause pollution problems, recent attention has focused on NOx compounds which are in part responsible for acid rain. Attempts to control, reduce or eliminate the pollutants in exhaust gases have included mechanical, electrical and chemical apparatus.

One known method of reducing pollutants is by means of chemical apparatus such as catalytic converters. Such devices are typically used with internal combustion engines such as those found in automobiles. In a catalytic converter system, engine exhaust gases are mixed with air and the mixture then passes through a catalyst bed. In the catalyst bed, pollutants in the exhaust gas react with the air in the mixture to produce more complete combustion. Such devices have drawbacks. For example, they restrict the exhaust gas flow and therefore increase the exhaust back-pressure on the internal combustion engine, resulting in reduced efficiency and fuel economy.

- 2 -

Further, the catalyst must be replaced at regular intervals to maintain conversion efficiency, thus increasing maintenance expense. In addition, such catalytic converters are not known to efficiently reduce NOx pollutants. Consequently, additional techniques are generally used in conjunction with the converter systems to reduce NOx pollutants. These additional techniques generally take the form of recirculating a portion of the engine exhaust gases through the engine to reduce combustion temperatures. However, these additional techniques further reduce fuel efficiency and economy and require additional equipment.

Other proposals to reduce pollution to a satisfactory level have involved the application of electric fields to the pollutant-containing exhaust gas. Such proposals involve mixing air with the exhaust gases, and then subjecting the mixture to an electric field which may take the form of a spark, an electric arc, electric plasma, a corona or a silent discharge. The electric field must be sufficiently intense and of sufficient duration to create ozone within the exhaust gas which then reacts with the pollutants to dissociate the compounds or to form harmless compounds. Two attempts to use electrical discharge to reduce pollutants are shown in U.S. Patent Nos. 3,188,167 and 3,979,193.

Previously known electrical devices appear to have additional drawbacks. First, because of the intense electric field used in such devices, oxidation of nitrogen may actually increase the amount of NOx pollutants. Second, due to their construction, such devices typically increase exhaust back pressure, thereby reducing fuel economy and efficiency. Moreover, the addition of secondary air requires an air compressor, and this is a disadvantage because of the additional energy consumed.

- 3 -

It is an object of the present invention to provide a simple, efficient and economical exhaust gas treatment system in which exhaust gases are treated with a specially selected electric discharge to reduce harmful pollutants such as carbon monoxide, hydrocarbon and NOx emissions without producing significant back pressure in the exhaust system.

Disclosure of Invention

A method and apparatus are disclosed in which exhaust gases are passed through a treatment chamber and subjected to a relatively low-power alternating-current dielectric discharge for a selected time duration. The dielectric discharge, also known as a "silent discharge," is a capacitive discharge between electrodes, at least one of which is insulated. As a result, there can be no sparks or arcing between the electrodes. The discharge comprises the movement back and forth between electrodes of a cloud of electrons and ions that impact or slam into other molecules, dissociating those that are easiest to disrupt. Because of the fact that all nitrogen oxide gases have negative heats of formation, except at extremely high temperatures (1800° F. or above), these materials will be the easiest to dissociate.

A silent discharge is more efficient for ionizing gases than other forms of electrical discharge such as electric arcs, microwave or radio frequency plasmas. Moreover, a silent discharge is readily established essentially at any pressure from extremely low (less than one torr) to extremely high (many atmospheres). Accordingly, the placement of an appropriate array of alternately conductive and insulated electrodes in a gas stream will dissociate the nitrogen oxides in the stream. Additionally, the liberated monatomic oxygen will then oxidize any incompletely burned compounds in that stream.

- 4 -

In one embodiment of the invention, the dielectric discharge occurs between a first electrode encased in a dielectric and the chamber wall itself, which functions as a second electrode. In this manner, pollutants are oxidized and others are dissociated while the temperature of the exhaust gas is kept low enough to prevent the formation of new NO_x pollutants. The addition of secondary air is not required with the invention disclosed herein.

The discharge voltage is adjusted so that the temperature of the exhaust gas when increased in temperature by the electrical discharge nevertheless remains in a temperature region in which the heat of formation of nitrogen oxides is negative. This prevents new nitrogen compounds from being created by the discharge. The length of the treatment chamber is selected so that the exhaust gas remains in the electric discharge for a length of time suitable to dissociate the nitrogen compounds and oxidize carbon monoxide and hydrocarbons in the gas. Tests have indicated that a significant overall reduction in pollutants occurs using the invention disclosed herein.

Brief Description of Drawings

Fig. 1 shows an illustrative exhaust treatment chamber for applying a dielectric discharge to a fluid such as exhaust gas; and

Fig. 2 shows an illustrative voltage waveform of the alternating current discharge voltage showing areas where the discharge occurs.

Mode(s) For Carrying Out The Invention

Referring to Fig. 1, one embodiment of the present invention is disclosed and described in which gaseous fluids such as exhaust gases are treated by subjecting

- 5 -

them to a dielectric discharge. Treatment chamber 300 is a closed chamber which, illustratively, is cylindrical but may have other cross-section. The longitudinal wall 301 of chamber 300 is made of a conductive material such as steel. The ends 303 may be of the same material as wall 301, or may be another material such as fused quartz. The fluid or gas to be treated enters chamber 300 via an inlet port 310 and exits via an outlet port 312. Ports 310 and 312 will typically be of the same material as wall 301, although this is not a requirement. The precise locations of the inlet and outlet ports are not critical to the invention, but for illustration are located towards the end of the chamber 300 so that the fluid or gas enters the chamber perpendicularly to the axis of the chamber. As shown, the cross-section of chamber 300 is constant throughout its entire length so that the chamber does not cause a significant back pressure on the gas passing through it. Such a chamber may illustratively be mounted in the exhaust pipe of an internal combustion engine or in the exhaust stack of a fossil fuel power plant. The chamber may also be mounted in a muffler system. The diameter of the chamber can be adjusted to accommodate the volume of gas passing through it.

Mounted within chamber 300, preferably along its central axis, in one embodiment, is a tubular insulator structure 302. In order for a dielectric discharge to occur and to prevent arcing, the insulator structure 302 should remain an insulator over the entire operating temperature range of treatment chamber 300 which, if the chamber is used to treat exhaust gas generated by an internal combustion engine, for example, may be in the range of 1200° F. Thus, the materials used to fabricate tubular structure 302 should not be of the type which are insulators at room temperature but which become conductive at higher temperatures. In particular, the bulk

- 6 -

resistivity of the insulator structure 302 should remain greater than 10^9 ohm-cm throughout the operating temperature range. Such materials as fused quartz and boron nitride have been found to be satisfactory for
5 insulator 302.

To create an electric discharge within the chamber, two electrodes are necessary. One electrode is formed by the conductive chamber 300 itself. The second electrode 316 is formed on the inside surface of tubular structure
10 302. In one embodiment, for illustration, silver is deposited on the inside surface of structure 302. In another embodiment, a liquid electrode can be created by filling the tubular structure 302 with an electrically conductive acid solution such as sulfuric or acetic acid
15 in water.

A high-voltage alternating current power supply 308 is connected between the chamber wall 300 and electrode 316. The voltage generated by power supply 308 is adjusted to initiate and maintain a dielectric discharge between
20 electrode 316 and wall 300.

The electrical discharge will cause heating of the gas passing through it. In accordance with the invention, however, the temperature rise produced in the treated gas by the discharge is reduced so that the overall
25 temperature of the gas will remain in the temperature region where the heat of formation of nitrogen oxides is negative. At temperatures above this region, nitrogen oxides (NOx) will increase. This is accomplished by subjecting the treated gas to a relatively low intensity
30 discharge over a long time period rather than applying an intense discharge over a short time period as has been previously done. The active length 314 of chamber 300 and the frequency of high-voltage power supply 308 should be adjusted based on the flow velocity of the fluid through
35 the chamber so that the fluid is subjected to a plurality

- 7 -

of discharge cycles before completely passing through the chamber.

For example, above 1600° F., the heat of formation of polluting NOx compounds changes from negative to positive.

5 Exhaust gas produced by an internal combustion engine varies in temperature up to approximately 1200° F. Thus the discharge produced by power supply 308 must be adjusted such that the temperature rise produced by the discharge increases the gas temperature by no more than
10 400° F.

As shown in Figure 2, the voltage output of the high-voltage alternating current power supply 308 generally has sinusoidal voltage which varies between a positive maximum voltage v_{max} and a negative voltage, $-v_{max}$. The invention is
15 not limited to sinusoidal waveforms and will operate with any alternating current waveform. Since an electrical discharge occurs only when the voltage difference between chamber 300 and insulator structure 302 rises above the ionization potential of the treated gas, a discharge will
20 only occur in the shaded area 200 when the positive voltage difference exceeds the ionization potential, and in the shaded voltage area 202 when the negative voltage difference exceeds the ionization potential. Since the gas flows through chamber 300, the length 314 of chamber
25 300 and the frequency of power supply 308 must be adjusted based on the flow velocity in order to assure that the treated gas is subjected to a plurality of discharge cycles 200 and 202. Preferably, the length 314 of chamber 300 and the frequency of power supply 308 should be
30 adjusted such that the treated gas is subjected to at least eight half-cycles 200 and 202 on its passage through chamber 300. Thus, because a typical exhaust gas flow velocity from an internal combustion engine can reach 200 feet/second, if the gas passes through a treatment chamber
35 having an effective length of three feet, the treatment

- 8 -

time is about 15 milliseconds. The frequency of the power supply should therefore be higher than that typically used in the past, at or above approximately 300 Hz, to assure proper gas treatment. In practice, the frequency of power supply 308 will be on the order of 400 Hz to 40,000 Hz.

Additional elements may be added to the disclosed device to further enhance its pollution reducing effectiveness. For instance, one electrode in the device may be coated with a catalyst to enhance its ability to reduce NOx emissions. In one illustrative example, the wall 301 of chamber 300 is made of steel and a catalyst plating 320, which preferably comprises rhodium but may comprise platinum or nickel, is applied to its inside surface. An alternative embodiment would be to make the walls 301 of chamber 300 of nickel, which itself is a catalyst. With such an arrangement, the catalyst would not cause the undue back pressure or pressure drop which current catalyst systems are known to create. In addition, a catalyst applied in this manner would not become poisoned because it would continuously be cleaned by the plasma.

In another pollution reducing enhancement, a high intensity ultraviolet light source, such as a circular source 322, can be located outside one or both ends of the chamber 300 so as to irradiate the gas as it flows through the chamber. When an ultraviolet light source 322 is used, the end 303 of chamber 300 should be a material transparent to ultraviolet light, such as fused quartz. A reflector 324 can also be added at the end of the chamber 300 to enhance the radiation placed into the chamber. Although not shown in Fig. 1, the ultraviolet light source can be placed at both ends of chamber 300 if desired. Ultraviolet light is known to reduce NOx emissions. In one test of the disclosed system using ultraviolet light, NOx emissions were reduced an additional twenty percent.

- 9 -

An exhaust gas treatment system has been constructed in accordance with the embodiment shown in Figure 1. Treatment chamber 300 was a cylindrical steel tube which had an overall length of four feet and an effective length

5 314 of three feet and a diameter of five inches. Structure 302 had a diameter of 3.5 inches and was constructed of fused quartz. Inlet and outlet pipes 310 and 312 were 3.5 inches in diameter. Power supply 308 was adjusted to produce a 3300 Hz alternating current output

10 with an output voltage of 60 kilovolts. The voltage of power supply 308 was adjusted such that the temperature of the exhaust gas, including the increase due to the discharge, remained below 1600° F. and the power applied was approximately 60 watts.

15 An experimental model of the exhaust gas treatment system was connected to receive exhaust from one cylinder of an L-10 diesel engine manufactured by the Cummins Engine Company, Columbus, Indiana. Table I below shows the hydrocarbon and NOx emissions as measured by the

20 Cummins Technical Center of Columbus, Indiana at the output 312 of the treatment system without high-voltage supply 308 operating.

TABLE I

	Hydrocarbons	205 ppm.
25	NOx	597
	RPM	732

Table II shows a 46% reduction in hydrocarbon and a 38% reduction in NOx emissions when power supply 308 was operative, causing the exhaust gas treatment system to be

30 operative.

TABLE II

	Hydrocarbons	113 ppm.
	NOx	369
	RPM	732

- 10 -

Although an embodiment of the invention has been illustrated and described, it is anticipated that various changes and modifications, including, without limitation, multiple electrodes, will be apparent to those skilled in the art, and that such changes may be made without departing from the scope of the invention as defined by the following claims:

- 11 -

What Is Claimed Is:

1. A method for reducing pollutants including NOx compounds in a moving fluid, said method comprising the steps of:
 - 5 providing a closed treatment chamber having a length and an input and output and comprised of a conductive material sufficient to make said treatment chamber a first electrode;
 - 10 providing a dielectric insulating element within said treatment chamber;
 - placing within said dielectric insulating element conductive material sufficient to create a second electrode;
 - 15 generating an alternating current electric field between said first and second electrodes;
 - directing said moving fluid through said treatment chamber and said electric field; and
 - adjusting the frequency and strength of said electric field so that a dielectric discharge occurs
 - 20 while said field strength remains low enough that the temperature of said moving fluid remains in the temperature range where the heat of formation of said NOx compounds is negative.
2. The method according to claim 1, further including the
25 step of:
 - adjusting said treatment chamber length and said alternating current frequency such that said moving fluid is subjected to at least eight half-cycles of said discharge while in said treatment chamber.
- 30 3. A method for reducing pollutants, including NOx compounds, in a moving fluid in a closed treatment chamber having a length and at least one pair of

- 12 -

electrodes separated by an insulator, said method comprising the steps of:

directing said fluid through said chamber;

5 applying an alternating current electrical field
across said electrodes to cause a dielectric discharge
to occur between said electrodes, said field having a
frequency and a strength low enough that the
temperature of said fluid remains in the temperature
range where the heat of formation of said NOx
10 compounds is negative; and

adjusting said treatment chamber length and said
alternating current frequency such that said fluid is
subjected to at least eight half-cycles of said
discharge while in said treatment chamber.

15 4. The method according to claim 3, wherein said first
electrode comprises said treatment chamber, and said
second electrode comprises an electrical conductor
located inside a dielectric insulator placed within
said treatment chamber.

20 5. The method according to Claim 4, wherein a portion of
the inside of said treatment chamber comprises a
catalyst.

6. The method according to Claim 4, further including an
ultraviolet light source positioned such that said
25 moving fluid passes through the light emitted from
said light source.

7. The method according to Claim 3, further including an
ultraviolet light source positioned such that said
moving fluid passes through the light emitted from
30 said light source.

- 13 -

8. Apparatus for reducing pollutants, including NOx compounds, in a moving fluid, said apparatus comprising:

5 a treatment chamber having an inlet and an outlet through which said moving fluid passes and comprised of a conductive material sufficient to form a first electrode;

10 a tubular element within said treatment chamber positioned such that said moving fluid passes between said tubular element and said first electrode, said tubular element comprising a dielectric insulating material and having a conductive material located within said tubular element to form a second electrode;

15 means for generating an alternating current electrical field between said first and second electrodes having a strength high enough that a dielectric discharge occurs between said electrodes, and low enough that the temperature of said moving
20 fluid remains in the temperature range where the heat of formation of said NOx compounds is negative.

9. Apparatus according to Claim 8, wherein a portion of said treatment comprises a catalyst.

25 10. Apparatus according to Claim 8, further including an ultraviolet light source positioned such that said moving fluid passes through the light emitted from said light source.

30 11. Apparatus according to Claim 9, further including an ultraviolet light source positioned such that said moving fluid passes through the light emitted from said light source.

- 14 -

12. Apparatus according to Claim 8, wherein said treatment chamber is cylindrical and said fluid passes longitudinally through said chamber.
- 5 13. Apparatus according to Claim 12, wherein said insulating material is fused quartz or boron nitride.
- 10 14. Apparatus according to Claim 13, wherein said treatment chamber is of a length and said electric field has a frequency such that said moving fluid is subjected to at least eight half-cycles of electric discharge while in said treatment chamber.
- 15 15. Apparatus for reducing pollutants, including NOx compounds, in a moving fluid, said apparatus comprising:
- 15 a cylindrical treatment chamber comprised of an electrically conductive material sufficient to form a first electrode, said chamber having an inlet and an outlet and an axis;
- 20 a tubular insulator structure located in said chamber along said chamber axis and passing through said chamber;
- a second electrode located on the inside of said tubular insulator structure;
- a power supply for generating an alternating current voltage; and
- 25 means for applying said electrical voltage to said first and second electrodes to create an electric field within said chamber, said field having a strength sufficient that a dielectric discharge occurs between said first and second electrodes, but said
- 30 field strength being low enough that the temperature of said fluid remains in the temperature range where

- 15 -

the heat of formation of said NOx compounds is negative.

16. Apparatus according to Claim 15, wherein a portion of said treatment chamber comprises a catalyst.
- 5 17. Apparatus according to Claim 16, further including an ultraviolet light source positioned such that said moving fluid passes through the light emitted from said light source.
- 10 18. Apparatus according to Claim 17, further including an ultraviolet light source positioned such that said moving fluid passes through the light emitted from said light source.
- 15 19. Apparatus for treating pollutants in a moving fluid according to Claim 17 wherein said insulator structure is comprised of fused quartz or boron nitride.

- 1/1 -

Fig. 1





Fig. 2



SUBSTITUTE SHEET

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
Int.Cl. 5 B01D53/32; B01D53/36; B01J19/08		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	B01D ; B01J ; F01N	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ⁹	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	DE,A,3 642 472 (BBC BROWN BOVERI AG) 23 June 1988 see claims 1-10; figure 2 ----	1,5,6, 8-12
A	US,A,3 862 043 (HAAKENSON) 21 January 1975 see claims 1-3; figure 3 ----	1,8,12, 13
A	DE,A,3 644 090 (BBC BROWN BOVERI AG) 7 July 1988 see claims 1,5,6,10; figure ----	1,5,8,9, 12
A	DATABASE WPI, NO. 75-29620W DERWENT PUBLICATIONS LTS, LONDON, GB & JP-A-50010275 (SUMITOMO METAL) 01-02-1975 *ABSTRACT* ----	1
<p>⁹ Special categories of cited documents :¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
31 AUGUST 1992	21.09.92	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	CUBAS ALCARAZ J. L.	

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. US 9203490
SA 60000**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 31/08/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-A-3642472	23-06-88	None	
US-A-3862043	21-01-75	None	
DE-A-3644090	07-07-88	None	

EPO FORM P0479

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82